

## ULTRASUEDE®: INVINCIBLY LUXURIOUS

The beauty of the finest suede meets the performance of the world's most advanced Ultra-microfiber in Ultrasuede®.

Engineered to satisfy the most demanding specifications, Ultrasuede® is as easy care as it is versatile. It's perfect for applications ranging from high-end contract and exclusive high-end contract and exclusive residential furnishings to first-class aircraft seating and yacht interiors.

- Soft, plush suede hand
- As ideal for wall covering as it is for upholstery
- Soothing to the touch in any climate
- Excellent colorfastness
- Resists sagging, stiffening, crocking, pilling and shrinking
- Highly abrasion-resistant; surpasses 200,000 Wyzenbeek double rubs
- Spot-cleanable and washable
- Unsurpassed range of today's most sought-after colors

## Care Instructions

**GENERAL CARE:** The luxurious feel and lustrous look of Ultrasuede® can be maintained with regular, light brushing with a medium bristle brush.

**STAIN REMOVAL** Ultrasuede® is inherently stain resistant. Most stains can be removed with water and a mild detergent. When required (see below), use a mild cleaning fluid available at any local hardware store.

TYPE OF STAIN	MILD DETERGENT	MILD CLEANING FLUID
Coffee, Tea	√	
Red Wine, Liquor	√	
Cake, Soft Drinks	√	
Milk	√	
Ketchup	√	
Steak Sauce, Soy Sauce	√	
Mayonnaise, Butter	√	√
Salad Oil	√	√
Chocolate	√	√
Cosmetic Foundation	√	√
Lipstick	√	√
Face Cream	√	√
Suntan Oil/Lotion	√	√
Shoe Polish	√	√
Machine Oil		√

## SPECIFICATIONS

Style: 862

Width: 54-55"

Composition:  
100% polyester ultra-microfiber  
non-woven with non-fibrous  
polyurethane binder

Put-up: 33 yd. R.O.T

Weight: Approx. 11.1 oz per square  
yard

Thickness: 1 millimeter

### CHARACTERISTICS MEETS OR EXCEEDS

Abrasion:	ASTM 3597 (7.4) Wyzenbeek 200,000 double rubs
Air Permeability:	ASTM D 737
FIR Rating:	CA Bulletin 117-Class I ASTM. E84 Class A UFAC-Class 1 Rating Can be treated to meet FMVSS302 Specifications
Pilling Resistance:	ASTM D 3512-96
Tensile Strength:	ASTM D 5034-95
Tear Strength:	ASTM D 5733-95
Dimensional Stability:	ASTM D 3597-95a (7.5)

ultrasuede®  
*Ambiance*

'TORAY'

Ultrasuede is a registered trademark of Toray Ultrasuede (America), Inc.